



## Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 82362

### \*\*\* Section 1 - Identification \*\*\*

#### Product Identifier

SAFETY-KLEEN ETHYL ACETATE

#### Product Code

1021789

#### Synonyms

Acetic Esther

#### Recommended Use

Solvent for chemical intermediates (oils, gums, resins)

#### Restrictions on Use

If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

#### Manufacturer Information

Safety-Kleen Systems, Inc.  
2600 North Central Expressway  
Suite 200  
Richardson, Texas, 75080

Phone: 1-800-669-5740  
[www.safety-kleen.com](http://www.safety-kleen.com)

Emergency # 1-800-468-1760

#### Issue Date

April 4, 2019

#### Supersedes Issue Date

May 20, 2015

#### Original Issue Date

June 6, 2009

### \*\*\* Section 2 - Hazard(s) Identification \*\*\*

#### Classification in Accordance with 29 CFR 1910.1200.

Flammable Liquids, Category 2

Acute Toxicity (Inhalation), Category 3

Eye Damage / Irritation, Category 2A

Specific Target Organ Toxicity - Single Exposure, Category 3

Specific Target Organ Toxicity - Single Exposure, Category 1 (liver and kidneys)

#### GHS LABEL ELEMENTS

##### Symbol(s)



#### Signal Word

DANGER!

#### Hazard Statement(s)

Highly flammable liquid and vapor

Toxic if inhaled.

Causes serious eye irritation

May cause drowsiness and dizziness

May cause respiratory irritation

Causes damage to liver and kidneys.

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## Precautionary Statement(s)

### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe vapor or mist. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

### Response

In case of fire, use media appropriate for extinction. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### Storage

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### Disposal

Dispose of in accordance with all applicable federal, state and local regulations.

## \*\*\* Section 3 - Composition / Information on Ingredients \*\*\*

CAS	Component	Percent
141-78-6	Ethyl acetate	97-100
67-64-1	Acetone	0-2.5

## \*\*\* Section 4 - First Aid Measures \*\*\*

### Description of Necessary Measures

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Ingestion

IF SWALLOWED: Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything by mouth to an unconscious person.

### Most Important Symptoms/Effects

#### Acute

Toxic if inhaled, eye irritation, respiratory tract irritation, central nervous system depression, kidney damage, liver damage

#### Delayed

No information on significant adverse effects.

### Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

Treat symptomatically and supportively. Administration of gastric lavage, if warranted, should be performed by qualified medical personnel. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## \*\*\* Section 5 - Fire-Fighting Measures \*\*\*

### Suitable Extinguishing Media

Carbon dioxide, alcohol-resistant foam, dry chemical, water spray, or water fog.

### Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

### Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Avoid friction, static electricity and sparks. Product may be sensitive to static discharge, which could result in fire or explosion. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Vapors may cause drowsiness and dizziness. Fire may produce irritating, poisonous and/or corrosive fumes. Runoff to sewer may cause a fire or explosion hazard. Containers may rupture or explode. Empty containers may contain product residue.

### Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.

### Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

### Fire Fighting Measures

Keep storage containers cool with water spray.

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

### Personal Precautions, Protective Equipment and Emergency Procedures

Remove all ignition sources. Do not touch or walk through spilled material. Stop leak if possible without personal risk. Wear personal protective clothing and equipment, see Section 8. Keep unnecessary people away, isolate hazard area and deny entry. Ventilate the area. Avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors.

### Methods and Materials for Containment and Clean Up

Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Do not allow product to enter sewer or waterways.

Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see **Section 15**.

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Precautions for Safe Handling

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke when using this product. Wash thoroughly after handling.

### Conditions for Safe Storage, Including Any Incompatibilities

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition; containers may explode and cause injury or death. Empty product containers may retain product residue and can be dangerous. See **Section 14** for Packing Group information.

### Incompatibilities

Strong acids, strong bases, strong oxidizer

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

### Component Exposure Limits

<b>Acetate, ethyl</b>	<b>141-78-6</b>
ACGIH:	400 ppm TWA
NIOSH:	400 ppm TWA ; 1400 mg/m <sup>3</sup> TWA ; 2000 ppm IDLH (10% LEL )
OSHA (US):	400 ppm TWA ; 1400 mg/m <sup>3</sup> TWA
<b>Acetone</b>	<b>67-64-1</b>
ACGIH:	250 ppm TWA; 500 ppm STEL
NIOSH:	250 ppm TWA ; 590 mg/m <sup>3</sup> TWA; 2500 ppm IDLH (10% LEL )
OSHA (US):	1000 ppm TWA ; 2400 mg/m <sup>3</sup> TWA

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

#### Acetone (67-64-1)

25 mg/l Medium: urine Time: end of shift Parameter: Acetone (nonspecific )

### Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Safety glasses with side shields should be worn at a minimum. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

#### Respiratory Protection

It is not expected that using this product as recommended would require wearing a respirator. If ventilation is not sufficient to effectively prevent buildup of mists or vapors, appropriate respiratory protection must be provided. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.1 requirements must be followed whenever workplace conditions warrant a respirator's use.

#### Glove Recommendations

Where skin contact is likely, wear chemical impervious gloves. Use of the following gloves types is NOT recommended: polyvinyl alcohol (PVA), polyvinyl chloride (PVC), nitrile or equivalent gloves. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

#### Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses. Gloves. Lab coat or apron.

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Appearance/Odor :</b>	Clear, colorless liquid, slightly fruity odor	<b>pH:</b>	Not applicable
<b>Boiling Point:</b>	171°F (77°C)	<b>Odor Threshold:</b>	50 ppm
<b>Solubility (H2O):</b>	Slight.	<b>Melting Point:</b>	-119°F (-84°C)
<b>Density:</b>	7.5 LB/US gal (900 g/l)	<b>Specific Gravity:</b>	0.90 (water =1)
<b>Evaporation Rate:</b>	6.2 (butyl acetate =1)	<b>Octanol/H2O Coeff.:</b>	Log Pow = 0.73
<b>Auto Ignition Temperature:</b>	799°F (426°C)	<b>Molecular Weight:</b>	88.1
<b>Flash Point:</b>	25°F (-4°C) Closed Cup; 45°F (7°C) Open Cup	<b>LFL:</b>	2 VOL%
<b>Viscosity:</b>	<4000.0	<b>UFL:</b>	11.5 VOL%
<b>Flammability Class:</b>	Flammable	<b>Vapor Pressure:</b>	73 mm Hg at 68°F (20°C)
<b>Percent Volatile:</b>	100 WT% As per 40 CFR Part 51.100(s)	<b>Vapor Density:</b>	3 (air = 1)
<b>Flash Point Method:</b>	Closed Cup	<b>Freezing Point:</b>	-119°F (-84°C)

## \*\*\* Section 10 - Stability & Reactivity \*\*\*

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.

### Possibility of Hazardous Reactions

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

### Conditions To Avoid

Avoid heat, sparks, or flame.

### Incompatible Materials

Avoid acids, alkalies, oxidizing agents, reactive halogens, or reactive metals.

### Hazardous Decomposition Products

None under normal temperatures and pressures. See also **Section 5**.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Information on Likely Routes of Exposure

#### Inhalation

Toxic if inhaled, May cause respiratory irritation. May cause drowsiness or dizziness.

#### Skin Contact

May cause irritation of the skin.

#### Eye Contact

Causes serious eye irritation.

#### Ingestion

Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

#### Acetate, ethyl (141-78-6)

Oral LD50 Rat 5620 mg/kg; Dermal LD50 Rabbit >18000 mg/kg; Inhalation LC50 Rat 4000 ppm 4 h

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg; Dermal LD50 Rabbit >15700 mg/kg; Inhalation LC50 Rat 50100 mg/m<sup>3</sup> 8 h

### Product Toxicity Data

#### Acute Toxicity Estimate

No data available.

#### Immediate Effects

Toxic if inhaled. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs), may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects; and/or liver and kidney damage. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death. May cause, eye irritation with redness, tearing, pain and/or blurred vision. May cause, skin irritation, redness, and/or drying. This product is not likely to be absorbed through the skin in harmful amounts. In rare instances, repeated skin contact with ethyl acetate may cause sensitization. May be harmful if swallowed. May cause, throat irritation, nausea, vomiting, central nervous system effects as noted for inhalation. Aspiration hazard: breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

#### Delayed Effects

Prolonged or repeated inhalation may cause toxic effects as noted under Acute inhalation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis). In rare instances, repeated skin contact with ethyl acetate may cause sensitization. Prolonged or repeated exposure may have reproductive toxicity or mutagenic effects. Ethyl acetate and acetone have demonstrated animal effects of mutagenicity. Acetone has demonstrated animal effects of reproductive toxicity.

#### Irritation/Corrosivity Data

Causes serious eye irritation. May cause skin irritation. May cause respiratory irritation.

#### Respiratory Sensitization

No information available for the product.

#### Dermal Sensitization

In rare instances, repeated skin contact with ethyl acetate may cause sensitization.

#### Component Carcinogenicity

Acetone	67-64-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

#### Germ Cell Mutagenicity

Repeated or prolonged exposure may cause mutagenic effects. Ethyl acetate and acetone have demonstrated animal effects of mutagenicity.

#### Tumorigenic Data

No data available

#### Reproductive Toxicity

Prolonged or repeated exposure may cause reproductive effects. Acetone has demonstrated animal effects of reproductive toxicity.

#### Specific Target Organ Toxicity - Single Exposure

Eye, skin, kidneys, liver, central nervous system, respiratory tract.

#### Specific Target Organ Toxicity - Repeated Exposure

Eye, skin.

#### Aspiration hazard

Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

#### Medical Conditions Aggravated by Exposure

Individuals with pre-existing cardiovascular, liver, kidney, respiratory tract (nose, throat, and lungs), central nervous system, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## \*\*\* Section 12 - Ecological Information \*\*\*

### Component Analysis - Aquatic Toxicity

Acetate, ethyl	141-78-6
Fish:	LC50 96 h Pimephales promelas 220 - 250 mg/L [flow-through ]; LC50 96 h Oncorhynchus mykiss 484 mg/L [flow-through ]; LC50 96 h Oncorhynchus mykiss 352 - 500 mg/L [semi-static ]
Invertebrate:	EC50 48 h Daphnia magna 560 mg/L [Static ] EPA
Acetone	67-64-1
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static ]; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [Static ] EPA ; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID

### Persistence and Degradability

No information available for the product.

### Bioaccumulative Potential

No information available for the product.

### Mobility

No information available for the product.

### Other Toxicity

No additional information available.

## \*\*\* Section 13 - Disposal Considerations \*\*\*

### Disposal Methods

Dispose of in accordance with all applicable federal, state and local regulations. Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product.

### Component Waste Numbers

Acetate, ethyl	waste number U112 (Ignitable waste )
----------------	--------------------------------------

## \*\*\* Section 14 - Transport Information \*\*\*

### US DOT Information:

Shipping Name: ETHYL ACETATE

Hazard Class: 3

UN/NA #: UN1173

Packing Group: II

Required Label(s): 3 FLAMMABLE LIQUID

### IATA Information:

Shipping Name: ETHYL ACETATE

Hazard Class: 3

UN#: UN1173

Packing Group: II

Required Label(s): 3

# Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

## IMDG Information:

Shipping Name: ETHYL ACETATE

Hazard Class: 3

UN#: UN1173

Packing Group: II

Required Label(s): 3

## TDG Information:

Shipping Name: ETHYL ACETATE

Hazard Class: 3

UN#: UN1173

Packing Group: II

Required Label(s): 3 FLAMMABLE LIQUID

## International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Acetate, ethyl	141-78-6
IBC Code:	Category Z

## Further information

Emergency Response Guidebook reference: 129

## \*\*\* Section 15 - Regulatory Information \*\*\*

### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Acetate, ethyl	141-78-6
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
Acetone	67-64-1
CERCLA:	5000 lb final RQ ; 2270 kg final RQ

### SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Acetate, ethyl	141-78-6	Yes	Yes	Yes	Yes	Yes
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes

### California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.



## Safety Data Sheet

Material Name: SAFETY-KLEEN ETHYL ACETATE

SDS ID: 89039

### Component Analysis - Inventory Acetate, ethyl (141-78-6)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
Yes			Yes	Yes	Yes	Yes	Yes	Yes

### Acetone (67-64-1)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

### \*\*\* Section 16 - Other Information \*\*\*

**NFPA Ratings: Health: 2 Fire: 3 Reactivity: 0**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

#### Summary of Changes

Regulatory review and update.

#### Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

#### Disclaimer

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.